


MAIN FEATURES


Hollow shaft encoder series for industrial applications with high mechanical resistance requirements. These encoders are designed to withstand high radial and axial shaft loads.

- 3 channel encoder (A / B / Z) up to 24000 ppr
- Power supply up to +30 V DC with various electrical interfaces available
- Output frequency up to 500 kHz
- Cable or connector output
- Metal cover available for heavy duty applications
- Blind hollow shaft diameter up to 15 mm
- Mounting by stator coupling, torque stop slot or torque pin




ORDERING CODE	ER	58F	M*	500	S	5/28	P	8	X	3	M	R	.162	+XXX
SERIES incremental encoder series ER														
MODEL blind hollow shaft with stator coupling 58F blind hollow shaft with torque stop slot 63F blind hollow shaft with torque pin 63G														
METAL COVER * add for metal cover M														
RESOLUTION ppr from 100 to 24000 refer to the available pulses list														
ZERO PULSE without zero pulse S with zero pulse Z														
POWER SUPPLY (with L electrical interface) 5 V DC 5 5 ... 28 V DC 5/28														
ELECTRICAL INTERFACE NPN open collector C push-pull P line driver L power supply 5/28 V DC - output RS-422 RS														
BORE DIAMETER mm 8 mm 10 mm 12 mm 14 mm 15														
ENCLOSURE RATING IP 54 X IP 66 S														
MAX ROTATION SPEED 3000 rpm 3														
OUTPUT TYPE cable (standard length 1,5 m) P preferred cable lengths 2 / 3 / 5 / 10 m, to be added after DIRECTION TYPE (eg. PR5) MIL plug connector M JIS-C-5432 IP40 plug connector J M12 plug connector M12 M23 plug connector H M16 IP40 plug connector C														
DIRECTION TYPE axial A radial R														
SOCKET socket not included .162 to be reported only with connector output (eg. MR.162), for socket see Accessories														
VARIANT custom version XXX														

58F




63G




torque pin is included in model G, for model F please refer to Accessories
recommended mating shaft tolerance g6
dimensions in mm

dimensions in mm


63F



DIMENSIONS WITH METAL COVER AND RADIAL OUTPUT



DIMENSIONS WITH METAL COVER AND AXIAL OUTPUT



ELECTRICAL SPECIFICATIONS

Resolution	from 100 to 24000 ppr
Power supply¹	5 = 4,5 ... 5,5 V DC 5/28 = 4,5 ... 30 V DC (reverse polarity protection)
Power draw without load	0,8 W max
Max load current	C / P = 50 mA / channel L / RS = 20 mA / channel
Electrical interface²	NPN open collector (AEIC-7273, pull-up max +30 V DC) push-pull / line driver HTL (AEIC-7272 or similar) line driver RS-422 (AELT-5000 or similar)
Max output frequency	250 kHz up to 6000 ppr / 500 kHz from 7200 ppr
Counting direction	A leads B clockwise (shaft view)
Index signal	180°e (gated A)
Mean time to dangerous failure (MTTF_d)³ according to EN ISO 13849-1	263 years
Mission time (Tm)³	20 years
Diagnostic coverage (DC)³	0%
Cable type	shielded - fixed installation conductors section 0,22 mm ² / AWG 24 bending radius min 60 mm
Electromagnetic compatibility	according to 2014/30/EU directive
RoHS	according to 2011/65/EU directive
UL / CSA	file n. E212495

RESOLUTIONS

100 - 120 - 128 - 150 - 200 - 240 - 250 - 256 - 300 - **360** - 400 - 480 - **500** - **512** - **600** - 625 - **720** - 800 - 900 - **1000** - **1024** - 1200 - 1250 - 1440 - 1600 - 1800 - **2000** - **2048** - **2500** - 3000 - **3600** - 4000 - 4096 - **5000** - 6000 - **7200** - 8000 - 8192 - 9000 - **10000** - 10240 - 12000 - **14400** - 16000 - 16384 - 18000 - **20000** - 20480 - 24000

please directly contact our offices for other pulses, preferred resolutions in bold

MECHANICAL SPECIFICATIONS

Bore diameter	ø 8* / 10* / 12* / 14 / 15 mm * with supplied shaft adapter (valid for resolution ≥ 3000 ppr)
Enclosure rating IEC 60529	X = IP 54 S = IP 66
Max rotation speed	3000 rpm
Shock	50 G, 11 ms (IEC 60068-2-27)
Vibration	10 G, 10 ... 2000 Hz (IEC 60068-2-6)
Moment of inertia	4 x 10 ⁻⁶ kgm ² (95 x 10 ⁻⁶ lbft ²)
Starting torque (at +20°C / +68°F)	< 0,02 Nm (2,83 Ozin) with X enclosure rating < 0,06 Nm (8,50 Ozin) with S enclosure rating
Bearing stage material	aluminum
Shaft material	stainless steel
Shaft adapter material	bronze
Housing material	PA66 glass fiber reinforced / painted aluminum
Bearings	n.2 ball bearings
Bearings life	10 ⁹ revolutions
Operating temperature^{4, 5}	-20° ... +70°C (-4° ... +158°F)
Storage temperature⁵	-25° ... +70°C (-13° ... +158°F)
Weight	350 g (12,35 oz) 450 g (15,87 oz) with metal cover

¹ as measured at the transducer without cable influences

² for further details refer to OUTPUT LEVELS on TECHNICAL BASICS section

³ this product is not a safety component, for further details refer to TECHNICAL BASICS section

⁴ measured on the transducer flange


⁵ condensation not allowed

CONNECTIONS


Function	Cable C / P	Cable L / RS	7 pin J C / P	7 pin J L / RS no Zero	7 pin M C / P	7 pin M L / RS no Zero	10 pin J L / RS with Zero	10 pin M L / RS with Zero	5 pin M12 C / P	8 pin M12 L / RS	12 pin H	5 pin C C / P	8 pin C L / RS
+V DC	red	red	6	4	F	D	4 - 5	D - E	2	7	12	5	7
0 V	black	black	1	6	A	F	6	F	4	1	10	1	8
A+	green	green	3	1	C	A	1	A	3	6	5	2	1
A-	/	brown or grey	/	3	/	C	7	G	/	5	6	/	2
B+	yellow	yellow	5	2	E	B	2	B	1	4	8	4	3
B-	/	orange	/	5	/	E	8	H	/	3	1	/	4
Z+	blue	blue	4	/	D	/	3	C	5	2	3	3	5
Z-	/	white	/	/	/	/	9	I	/	8	4	/	6
⏏	shield	shield	7	7	G	G	10	J	housing ¹	housing ¹	9	housing ¹	housing ¹

¹ only with metal cover


J connector (7 pin)
JIS-C-5432 IP40 Size 16
front view



M connector (7 pin)
Amphenol MS3102-E-16-S
front view



M12 connector (5 pin)
M12 A coded
front view




C connector (5 pin)
Amphenol C091 M16 IP40
front view




H connector (12 pin) - M23 CCW
Hummel 7.410.000000 - 7.002.912.603
front view




J connector (10 pin)
JIS-C-5432 IP40 Size 16
front view



M connector (10 pin)
Amphenol MS3102-E-18-1
front view



M12 connector (8 pin)
M12 A coded
front view



C connector (8 pin)
Amphenol C091 IP40 IEC 60130-9
front view

